

Easy Washing Automatic Gummy Depositing Line, Jelly Candy Machine 35-55 Stroke/Min

Specifications :

Payment Terms	L/C T/T Western Union
Keyword	advance gummy production line, Gummy Machine

Detail Introduction :

Automatic Gummy Depositing Line

Product Description



Automatic Gummy Depositing Line is a part of the Gummy Machine, SINOFUDE automatic gummy depositing line design with sanitary and easy washing structure for Gummy candy with CBD or THC or Vitamin and Minerals. Etc functional products. Automatic gummy depositing line is ideal

equipment that can produce good quality gummies with the saving of both the manpower and the space occupied. Optional with Touch screen, SERVO and PLC for Automatic operation, one shot system can make one color, two color or multi-color, center filled Gummy candy also available just change the manifold and nozzles. The cooling tunnel includes automatic Chain type/Air Knife/Brush de-molding system as option.

The automatic gummy depositing line complete line was designed according to pharmaceutical machine standard, higher level sanitary structure design and fabrication, all stainless steel materials are SUS304 and SUS316L in the line and it can be equipped with UL certified or CE certified components for CE or UL certificated and FDA proved.



Automatic Gummy Depositing Line FLOW CHART:

Syrup making? mixing?with gelatin or pectin with CBD or THC or Vitamin and Minerals??Stirring and holding? transporting? depositing ? cooling ? de-moulding ?following disposalà Glazing or sugar coatingà packing



Model	CLM80Q-A	CLM150-A	CLM300-A	CLM600-A	CLM1000-A
Capacity (kg/h)	60~80	150	300	600	1000
Speed (n/min)	Depend	35~55 stroke/min			
Candy weight (g):	As per candy size				
Electric power (kW)	19	12	18	36	68
Chilling (option)	Depend	8HP	12HP	16HP	30HP
Compressed air	0.6m3/min	0.5m3/min	0.8m3/min	1.0m3/min	1.2m3/min
C-Air pressure	0.4-0.6 Mpa	0.4-0.6 Mpa	0.4-0.6 Mpa	0.4-0.6 Mpa	0.4-0.6 Mpa
Conditions					
1.Room temperature(?)	20~25C	20~25C	20~25C	20~25C	20~25C
2.Humidity (%)	45~55%	45~55%	45~55%	45~55%	45~55%
Machine Length (m)	10m	15m	15m	18m	22m
Gross weight (Kgs)	2000	5000	6000	9000	12000